

**PROMATIC**<sup>®</sup>

**PROFESSIONAL  
AEOSOL SYSTEM.**



*"It's the finish  
that counts"*

<https://westco-group.com/westco-tones/>

# PROMATIC®

PROMATIC® - PROFESSIONAL COATINGS AND FINISHES FOR THE DISCERNING PAINTER.

All the products in the range have been formulated with the highest quality ingredients to guarantee the best results every time.



## **SPRAYING TIPS**

**PREPARATION** - Surfaces need to be clean, dry and free of grease. Depending on the material, the surface needs to be derusted, filled, sanded and cleaned. Surfaces that are not to be painted need to be taped off with tape and paper, then the surfaces need to be primed. The ideal work temperature lies between +15 and +20°C. Avoid direct sunlight!

**SHAKE** - Shake the can vigorously for about 2 minutes starting from the time when the mixing balls can be heard in the can. This is very important to ensure that the coloured pigment is well stirred and mixed in. This is the only way to obtain the right paint colour.

**GETTING READY** - If possible spray outdoors, or in a well ventilated room (cellar, workshop or garage). Indoors you must cover the surrounding area well to protect it from the fine misting of spray paint. Mask any areas not to be painted. Good illumination is also important, to let you see whether you have painted over the whole area.

**SPRAYING** - When spray painting, always hold the can vertically. Check the colour tone by means of spray tests. Never spray straight away onto the object to be painted. Spray first onto a test piece e.g. a newspaper or masking material. Be sure to spray from the correct distance of 25 - 30cm. Different objects call for different spray techniques. Start spraying close to the object but not directly onto it. Press the actuator button down fully. Move the can slowly and evenly back and forth, changing direction only after the spray has moved past the object. This makes it easier to control the amount of paint falling onto the object and lets you ensure that too much paint does not build up, forming runs or 'tear drops'. Wait 2-3 minutes between the cross-coats. Don't try to get a perfectly smooth surface at the first pass. The first pass should be regarded as a preparatory coat on which you will build a smooth even finish with the second and perhaps third passes, spraying before the previous coat is fully dry, but with 1 or 2 minutes between each pass. Further coats can then only be applied after 24 hours, otherwise there is the risk of lifting.

**AFTER USE** - Turn the can on its head and spray the valve empty. This avoids the spray head from becoming blocked. For more information, please read the label on the can itself.

**PRODUCT**

**CODE, DESCRIPTION & BENEFITS**



**AZ500 ALU ZINC PRIMER 500ml**

A fast drying, high quality 'weld thru' bright zinc primer, suitable for repairing damaged galvanising. Offers good corrosion protection, resistance to petrol, chemicals and heat up to 250°C



**ZR500 ZINC RICH PRIMER 500ml**

A high quality 90% zinc rich primer which provides outstanding cathodic corrosion protection for all bare metals. Offers good corrosion protection, resistance to petrol, chemicals and heat up to 350°C



**EP500 ETCH PRIMER 500ml & 1L**

A fast drying etch primer providing excellent adhesion to difficult substrates such as aluminium and galvanised steel. The fully cured primer has a smooth, non-porous, 'weld thru' finish.



**SP400 SPRAY PUTTY AEROSOL 400ml**

A first-class spray putty that quickly and efficiently fills small imperfections, scratches and sanding marks. It gives a high opacity, smooth non-porous finish with good sanding properties for steel substrates. Very fast drying performance even when applied in thick coats.



**RP500 RAPID BUILD GREY PRIMER AEROSOL 500ml**

A one component primer filler, providing good filling properties with active protection against corrosion. This product is ideal as a primer filler for all metal substrates including aluminium and galvanised steel.

**P  
R  
I  
M  
E  
R  
S**

**PRODUCT**

**CODE, DESCRIPTION & BENEFITS**



**HB-1 RAPID BUILD GREY PRIMER 1L**

A single component fast drying, primer filler providing protection against corrosion and gives a good high build finish that can be overcoated with any top coat. The product offers a smooth, non porous finish that is easy to sand, wet and dry.



GP500 **REDP500** WP500 YP500

**GREY, RED, WHITE & YELLOW PRIMER AEROSOL 500ml**

A fast drying acrylic primer filler. Fast drying with good spraying properties and good coverage. Will adhere to wood, metal, aluminum and many other substrates



**PP500 & PP-1 PLASTIC PRIMER 500ml & 1L**

A clear adhesion promoter for substrates such as ABS, PVC, PP and other automotive plastics. Very fast drying, transparent and flexible. Can be over coated with any primer or topcoat.



**CL500 & CL-1 CLEAR LACQUER**

A high quality, scratch resistant, fast drying acrylic gloss clear coat, suitable for overcoating water and solvent based base coats. Suitable for internal and external use. Weather and UV resistant. The products provide excellent surface hardness and good elasticity that can be mechanically polished

**T  
O  
P  
C  
O  
A  
T  
S**



MB500 SB500 GP500 GW500

**MATT BLACK, SATIN BLACK, GLOSS BLACK, GLOSS WHITE AEROSOL 500ml**

A high quality, fast drying acrylic paint with good spray characteristics. Suitable for most surfaces. It gives a weather resistant, UV resistant, scratch and impact resistant finish that can be mechanically polished

**T  
O  
P  
C  
O  
A  
T  
S**

**PRODUCT**

**CODE, DESCRIPTION & BENEFITS**



**WS500 WHEEL SILVER & STW500 STEEL WHEELS AEROSOL 500ml**

A high quality, fast drying acrylic wheel paint for steel and aluminium rims and hub caps. Weather resistant and UV resistant with good colour and gloss retention.



**CR400 CHROME AEROSOL 400ml**

A fast drying, chrome effect spray. Can be applied to suitably prepared metal and plastics.

**H  
I  
G  
H  
T  
E  
M  
P**



HTB400 HTR400 HTS400 HTC400 HTW400

**BLACK, RED, SILVER, CLEAR, WHITE HIGH TEMPERATURE AEROSOL 400ml**

This range of high temperature aerosols provides resistance to temperatures of up to 800°C - except for HTR400 Red which is 300°C. They have good spray properties, have fast drying times and excellent adhesion.

**U  
N  
D  
E  
R  
...**



**CW500 CAVITY WAX (CLEAR) AEROSOL 500ml & 1L**

Cavity Wax gives an effective corrosion protection to vehicle cavities that are susceptible to rusting such as: door pillars, door skins, engine compartments, bonnets. It has excellent water repellent properties and the clear film is self regenerating providing on-going protection.

**B  
O  
D  
Y**

**PRODUCT**

**CODE, DESCRIPTION & BENEFITS**



**US500 BLACK UNDERBODY SCHUTZ AEROSOL  
500ml & 1L**

Underbody Schutz is a bitumen based product providing good corrosion resistance and an elastic, weatherproof, durable coating. This product is very thixotropic, idea for the underside of vehicles and wheel arches.

**B  
U  
M  
P  
E  
R  
S  
P  
R  
A  
Y  
S**



BSA400   BSB400   BSG400

**ANTHRACITE, BLACK, MID GREY BUMPERSPRAY  
AEROSOL 400ml**

A coloured, scratch resistant finish for interior and exterior plastic components such as bumpers and plastic trims. It has excellent coverage and adhesion, easy to apply and is fast drying. Can be applied directly onto most plastics.

**S  
T  
O  
N  
E  
C  
H  
I  
P**



SCB500   SCB-1   SCG500   SCG-1   SCW500   SCW-1

**STONECHIP BLACK, STONECHIP GREY,  
STONECHIP WHITE (all in 500ml & 1L)**

Stone Chip provides excellent corrosion protection for visible underside parts that are prone to stone chips and ultimately corrosion. The product is overcoatable and provides long lasting elasticity




**Pre-gassed Aerosol Can 400ml**

400ml aerosol requiring a 100ml fill of paint. Suitable for most solvent based paints. Contains DME and a solvent blend. Professional valve and nozzle system for great spray properties. One can, any colour.



DISTRIBUTED BY:  
WESTCO TONES

 315-5947

<https://westco-group.com/westco-tones/>