



## CW-1 CAVITY WAX

### QUALITY AND PROPERTIES

---

- Excellent penetration in difficult cavities
- Elimination and displacement of water already present
- Easy application
- Corrosion protection
- Excellent adhesion
- Resistant to weather effects, weak acids and alkalines

### PHYSICAL AND CHEMICAL DATA

---

- **Basis:** waxes, additives, free of aromatic solvents
- **Colour:** Transparent
- **Consistency:** liquid
- **Smell:** solvent
- **VOC-Content:** approx. 0.3230 kg
- **Salt spray test (DIN 50021):** >1000 hours, Ri 0 at 100µ dry layer
- **Chemical resistance against:** water, salt spray, oil, weak acids and bases
- **Temperature resistance (cured):** -25°C - +180°C
- **Working temperature:** +15°C - +25°C, best results at room temperature
- **Drying time (20°C, 65% RV):**  
Dust-dry: after approx. 105 minutes  
Completely dried: after approx. 5 h  
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Specific density (20°C)** (nach DIN 51757): 0.87 - 0.89 kg/ltr.
- **Storage stability:**  
5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** spray gun can, maximum nominal volume 1000 ml

### ENVIRONMENT AND LABELLING

---

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

**Labelling:** All products of Capella Solutions comply with the current status of their labelling regulations.

### USING INSTRUCTIONS

---

#### Application spray gun can:

- For best results bring can to room temperature.
- The product is ready-to-use, no thinner necessary.
- Clean the spray gun with white spirit

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

#### DISCLAIMER OF LIABILITY

The information contained in this Technical Data Sheet is correct to the best of Alpha Coatings Limited trading as Capella Solutions Group's ("Capella") knowledge, however, you must satisfy yourselves that the Goods are suitable for your needs by way of your independent testing or other processes. Capella makes no warranty, representation, or guarantee regarding the information contained in the Technical Data Sheet or the suitability of its products and services for any particular purpose, nor does Capella assume liability arising out of the application or use of the Goods other than any liability which cannot be limited by law including but not limited to liability for: (a) death or personal injury caused by negligence; (b) fraud or fraudulent misrepresentation; and (c) breach of the terms implied by section 12 of the Sales of Goods Act 1979, in such circumstances Capella's total liability shall not exceed the cost of the Goods. Capella's total liability includes liability in contract, tort, negligence, breach of statutory duty, or otherwise. It is the Customer's responsibility to ensure that the guidance on the Technical Data Sheet is followed.

Second Avenue, Chatham, Kent, ME4 5AU  
t: +44 (0)1634 823900 f: +44 (0)1634 813807  
e: sales@alphacoatings.co.uk