

PROTEXB is a premium textured coating restoring the structure of repaired plastic surfaces. Choice of two nozzles to allow the applicator to achieve the desired effect from the same aerosol.

Suitable substrates (cleaned & abraded)


- Suitably prepared Plastics - PP, PP/EPDM, ABS.
- For ultimate adhesion to plastics, ProXL Plastigrip should be applied first.

Physical and chemical data

Basis of binder	Vinylcopolymer resin
Colour	Black
Coverage	1.3 - 1.9m ²
Temperature resistance	
Storage stability	10 years in appropriate storage (-10°-25°C, relative air humidity of max. 60%)
Size	500ml
VOC content	305g/500ml

Application guide


- Remove all rust from metal surfaces
- Clean surface with a suitable degreaser then abrade
- Carry out test spray
- Areas to be sprayed must be free of grease, dust and dry
- For professional use only
- Wear an appropriate respirator



Shake aerosol for at least two minutes, after agitator ball is free



15-20 minutes @ 20°C



Apply in cross coats from distance of 250mm from object



Dust dry 10 minutes @ 20°C
Touch dry 30 minutes @ 20°C
The drying time depends on temperature, air humidity and thickness of the applied coat



The textured density and effect is dependent on the number of coats and the spraying distance. Apply several thin coats to get desired texture in conjunction with nozzle used.



After use, turn aerosol upside down and empty valve

Features and benefits

- Spot repair for all plastics
- Very durable finish
- Easy and quick to use
- Red nozzle fine/white nozzle coarse
- Suitable for interior and exterior

Environmentally sound

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.



DISCLAIMER OF LIABILITY

The information contained in this Technical Data Sheet is correct to the best of Alpha Coatings Limited trading as Capella Solutions Group's ("Capella") knowledge, however, you must satisfy yourselves that the Goods are suitable for your needs by way of your independent testing or other processes. Capella makes no warranty, representation, or guarantee regarding the information contained in the Technical Data Sheet or the suitability of its products and services for any particular purpose, nor does Capella assume liability arising out of the application or use of the Goods other than any liability which cannot be limited by law including but not limited to liability for: (a) death or personal injury caused by negligence; (b) fraud or fraudulent misrepresentation; and (c) breach of the terms implied by section 12 of the Sales of Goods Act 1979, in such circumstances Capella's total liability shall not exceed the cost of the Goods. Capella's total liability includes liability in contract, tort, negligence, breach of statutory duty, or otherwise. It is the Customer's responsibility to ensure that the guidance on the Technical Data Sheet is followed.